



<b>SWSB32X7-A1/A2</b> <b>SWSB32X8-A1/A2</b>		
<b>Features</b>	Panel Type	32" TFT FHD Panel
	Display Size (inch)	32"
	Number of pixels	1920 x 1080
	Active Display Area (mm)	697.4(H) x 391.85(V)
	Aspect Ratio	16:9
	Refresh rate	60 Hz
	Contrast Ratio (type)	1400:1 Static. 50 000:1 Dynamic
	Brightness (cd/m2)	300
	Peak White Luminance Ratio	95%
	Response time	8 ms
	Viewing Angle	178 / 178
	Color	1.07 Billion colors
	Operation Hour	7*24 Hours
	<b>Power and Eco Design</b>	Power Supply
Power Consumption		110 W
Power Consumption Stand-by		0.4 W
Lead presence		Yes
Mercury		0 mg
<b>Sound</b>	Loud Speaker	2 x 6W
<b>Dimension and Weight</b>	Outline Dimension	1358 x 454 x 450 mm
	Weight	28 kg
	Package Dimension	1500 x 550 x 175 mm
	Weight	32 kg
<b>SWSB32X7 OS (Optional configuration)</b>	Operating System	Android 11
	Processor	RK3568 (Cortex-A55,Quad-Core,up to 2.0GHz)
	GPU	Mali-G52 GPU supports OpenGL ES 1.1/2.0/3.2, OpenCL 2.0 and Vulkan 1.1
	RAM	Standard 2GB (Optional 4GB)
	Flash	Standard 32GB EMMC (Optional 64GB)
	Image rotation	Support 0 degree, 90 degree, 180 degree, 270 degree manual rotation
	USB	1 x USB 3.0 HOST, 1 x USB3.0 OTG
	TF Card	Data storage, maximum support 32G
	HDMI	1 x HDMI In HDMI1.4b /HDCP 1.4 480i/576i,480p/576p,720p/1080i /1080P/2160P
	4G	Support external 3G/4G USB dongle

	LAN	Support RJ45 R/A 1000M Ethernet, support Ethernet
	Audio	support 3.5mm audio output interface
	Multimedia	Video Support H.265, H.264, VP8, MAV, WMV, AVS, H.263, MPEG4 and other video formats Audio Support MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP and other formats Image Support various image formats such as JPG、BMP、PNG
	Wi-Fi	Support 2.4GHz/5GHz, Wi-Fi 6, support Wi-Fi 802.11b/g/n protocol; Support Bluetooth 5.0 Support Wi-Fi hotspot
SWSB32X8 (Standard)	HDMI	1 x HDMI HDMI1.4b /HDCP 1.4 480i/576i,480p/576p,720p/1080i /1080P
	USB	1 x USB 2.0 HOST USB Play list mode,USB Simple mode USB Auto play mode Video,USB Auto play mode Photo,USB Auto play mode Video/Photo
	Coaxial	1 x Coaxial Out 75Ω,0.5Vpp,PCM Audio
Environmental	Operating Temperature	0°C ~ 50°C
	Operating Temperature (Optional)	0°C ~ 80°C
	Storage Temperature	-20°C ~ 60°C
	Operating Ambient Humidity	10% ~ 80%
	Storage Humidity	5% ~ 90%
Accessories	Included	Remote control, Power cable

